


Operating System	m	
CAN bus	Interactive colour touch scr	een
Spoil Tank		
Litre Capacity		6000L
Spoil Door	Fully opening	
Door Operation	Hydraulic	
Door Lock	Six point hydraulic wedge locking mechanism	
Tipping	Telescopic hoist with safety	valve
Water Tank		
Clean Water Tank Capacity	Integrated	5000L
Clean Water Fill Type	Backflow protected Connection at ground level	50mm (2") camlock
Vacuum System		
Power Supply	Full engine horsepower via split shaft unit gear box	350Hp
Blower	Jurop Helix 750 Roots type rotary lobe, air injection	4162m ³ /h (2450cfm)
Filtration		
4 Stage Filtration System	Spoil tank, 3 barrel cyclone 12 poly washable filters & blower pre-filter	,
Suction Boom		
3 Function	Hydraulic 270° slew, boom up/down, boom stick in/out	5m reach
Travis Coupling		150mm (6")
Spoil Connection	n Points	
Spoil Tank Inlet	Travis with knife valve	150mm (6")
Spoil Tank Dewatering Drain	Travis with knife valve	150mm (6")
Boom Inlet	Travis	150mm (6")
NDD - High Pres	sure Water	
Pump	Comet TW8036S	1*
Pressure	2	248 Bar (360 <mark>0psi)</mark>
Flow		32LPM
Hose Size		10mm (3/8")
Hose Length		20m*
High Pressure Lance with Turbo Nozzle	e	1x 1500mm 1x 2000mm


Jetter Drain Cleaner		
Triplex Water Pump	Udor HXR1-C 250/160R	245LPM 151 Bar (2200psi)
Jetting Reel	Vacvator 180m of 1" Jetting hose	
Jetting Heads	ENZ Kit 1" BSP	
Remote Control	Pump on/off, reel in/out, vand pressure, hose length	
Remote		
Autec DJM Dynamic+	Proportional control joysti rocker leavers, e-stop, red	
Safety Equipment		
CAN bus Control System	Integrated safety shut down protection scales, e-stops, high water pressure, hydraulic oil temp, low transmission oil pressure, engine protection	
Emergency Stops	Control panel, Remote, LHS rear	3
Fire Extinguisher	Dry chemical ABE	4.5kg
Spoil Tank Safety Prop		Yes
Spoil Door Safety Prop		Yes
Safety Handrail & Maintanance Walkway	Pneumatically operated	Yes
Safety Harness Attachment Point		Yes
Beacons	Front & Rear	Yes
Work Lights	Rear of cab, end of boom rear of tank	ı & Yes
LED Light Bars	Left & right hand side	Yes
UHF 80 Channel		Yes
Storage		
Blower Frame Toolbox	Vertical three shelf	1m x 1m x .40m (400L)
Underbody Toolbox	.1	80m x .50m x .45m (160L)
Hose Trays	Left hand side	2.4m x .50m (480L)
Lockable Hose Tray (option)	Right hand side	2.4m x .50m (480L)
Vacuum Hose Reel	Vacvator - rear mounted, variable speed remote operated in/out	20m of 100mm (4") hose
Truck		

^{*} Option of two

Isuzu 300/350 FYJ 8x4

Unit Dimensions






Boom Reach

Minimum reach

Maximum reach



Description Code Wheelbase Α Rear Overhang В Overall Length С Unit Height D Overall Height Ε Overall Height - No Boom F Overall Width G 2490

Disclaimer: Photos for Illustration purposes, Vacvator Pty Ltd reserves the right to modify design and change equipment without previous notification.

HD 8-60 NDD-JET - Revision A.5