



<b>Operating Syste</b>	m	
CAN bus	Interactive colour touch scre	en
Spoil Tank		
Litre Capacity		40001
Spoil Door	Fully opening	
Door Operation	Hydraulic	
Door Lock	Four point hydraulic wedge locking mechanism	
Tipping	Telescopic hoist with safety	valve
Water Tank		
Clean Water Tank Capacity	Integrated	2000L
Clean Water Fill Type	Backflow protected Connection at ground level	50mm (2") camlock
<b>Vacuum System</b>		
Power Supply	Rear engine PTO	600N.m
Blower	Shandong, ZSH150V Roots type rotary lobe, air injection	
Filtration		
4 Stage Filtration System	Spoil tank, 2 barrel cyclone, 9 poly washable filters & blower pre-filter	
Suction Boom		
3 Function	Hydraulic 340° slew, boom up/down, boom stick in/out	5m reach
Travis Coupling		150mm (6")
Spoil Connection	n Points	
Spoil Tank Inlet	Travis with knife valve	150mm (6")
Spoil Tank Dewatering Drain	Travis with knife valve	150mm (6")
Boom Inlet	Travis	150mm (6")
<b>NDD - High Pres</b>	sure Water	
Pump	Comet TW8036S	1,
Pressure	2	48 Bar (360 <mark>0psi</mark>
Flow		32LPM
Hose Size		10mm (3/8")
Hose Length		20m
High Pressure Lance with Turbo		1x 1500mm & 1x 2000mm

Remote			
Wireless Remote	12 button, 24 function, variable speed, rechargeable batteries, emergency stop		
Safety Equipment			
CAN bus Control System	Integrated safety shut down protection scales, e-stops, high water pressure, hydraulic oil temp & engine protection		
Emergency Stops	Control pane <mark>l, Remote, LF</mark> RHS rear	IS rear, 4	
Fire Extinguisher	Dry chemical ABE	4.5kg	
Spoil Tank Safety Prop		Yes	
Spoil Door Safety Prop		Yes	
Safety Handrail & Maintanance Walkway	Pneumatically operated	Yes	
Safety Harness Attachment Point		Yes	
Beacons	Front & Rear	Yes	
Work Lights	Rear of cab, end of boom & rear of tank	Yes	
LED Light Bars	Left & right hand side	Yes	
UHF 80 Channel		Yes	
Storage			
Blower Frame Toolbox	Vertical three shelf	1m x 1m x .40m (400L)	
Underbody Toolbox		1m (250L)*	
Hose Trays	Left & right hand side	2.4m x .50m (480L)	
Lockable Hose Tray (option)	Left & right hand side	2.4m x .50m (480L)	
Vacuum Hose Reel	Vacvator - Rear mounted, variable speed remote operated in/out	40m (2x 20m) 100mm (4") hose)	
Truck			
Volvo FE818-350Hp 4x2	Automatic transmission & airbag suspension		

<sup>\*</sup> Option of two

## **Unit Dimensions**






Nozzle

Description	Code	Dimensions (mm)
Wheelbase	Α	5250
Rear Overhang	В	1775
Overall Length	С	8016
Unit Height	D	2650
Overall Height	E	3543
Overall Height - No Boom	F	3011
Overall Width	G	2500

**Boom Reach** 



Disclaimer: Photos for Illustration purposes, Vacvator Pty Ltd reserves the right to modify design and change equipment without previous notification.

Metro 4-40 NDD - Revision A.5