

Operating Syster	m	
CAN bus	Interactive colour touch scree	en
Spoil Tank		
Litre Capacity		7600L
Spoil Door	Fully opening	
Door Operation	Hydraulic	
Door Lock	Six point hydraulic wedge locking mechanism	
Tipping	Telescopic hoist with safety va	alve
Water Tank		
Clean Water Tank Capacity	Integrated	3000L
Clean Water Fill Type	Backflow protected Connection at ground level	50mm (2") camlock
Vacuum System	,	
Power Supply	Full engine horsepower via split shaft unit gear box	320Hp
Blower	Jurop Helix 750 Roots type rotary lobe, air injection	4162m³/h (2450cfm)
Filtration		
4 Stage Filtration System	Spoil tank, 3 barrel cyclone, 12 poly washable filters & blower pre-filter	
Suction Boom		
3 Function	Hydraulic 270° slew, boom up/down, boom stick in/out	5m reach
Travis Coupling		150mm (6")
Spoil Connection	n Points	
Spoil Tank Inlet	Travis with knife valve	150mm (6")
Spoil Tank Dewatering Drain	Travis with knife valve	150mm (6")
Boom Inlet	Travis	150mm (6")
NDD - High Press	sure Water	
Pump	Comet TW8036S	1*
Pressure	24	8 Bar (3600psi)
Flow		32LPM
Hose Size		10mm (3/8")
Hose Length		20m*
High Pressure Lance with Turbo Nozzle		1x 1500mm & 1x 2000mm

Remote		
Wireless Remote	12 button, 24 function, variable speed, rechargeable batteries, emergency stop	
Safety Equipment		
CAN bus Control System	Integrated safety shut down protection scales, e-stops, high water pressure, hydraulic oil temp, low transmission oil pressure & Hino engine protection	
Emergency Stops	Control panel, Remote & L	_HS rear 3
Fire Extinguisher	Dry chemical ABE	4.5kg
Spoil Tank Safety Prop		Yes
Spoil Door Safety Prop		Yes
Safety Handrail & Maintanance Walkway	Pnenumatically operated	Yes
Safety Harness Attachment Point		Yes
Beacons	Front & Rear	Yes
Work Lights	Rear of cab, end of boom & rear of tank	Yes
UHF 80 Channel		Yes
Storage		
Blower Frame Toolbox	Vertical three shelf	1m x 1m x .40m (400L)
Underbody Toolbox		1m (250L)
Hose Trays	Left & right hand side	2.4m x .50m (480L)
Lockable Hose Tray (option)	Left & right hand side	2.4m x .50m (480L)
Vacuum Hose Reel	Vacvator - rear mounted, variable speed remote operated in/out	20m of 100mm** (4") hose
Truck		
Hino 500 FM 2632 6x4	Allison automatic transmission, airbag suspension	


^{*} Option of two
** Option 40 metre hose


Boom Reach

Minimum reach

Maximum reach

Unit Dimensions





Description	Code	Dimensions (mm)
Wheelbase	А	5210
Rear Overhang	В	2440
Overall Length	С	9030
Unit Height	D	2870
Overall Height	E	3940
Overall Height - No Boom	F	3480
Overall Width	G	2490

Disclaimer: Photos for Illustration purposes, Vacvator Pty Ltd reserves the right to modify design and change equipment without previous notification.

Metro 6-76 NDD - Revision A.5